

**SENESE**

**Minimal Bottle Trap**

Installation Guideline

**senese.com**

Senese Srl p.iva 01602790527  
Loc. Frassi 34, 53011 Castellin in Chianti

## Minimal Bottle Trap

### Bottle Trap in Solid Brass

#### Article

|                 |   |
|-----------------|---|
| Polished Brass  | SESIFBOTMIN ON<br>240 Eur incl. VAT     |
| Polished Chrome | SESIFBOTMIN CR<br>285 Eur incl. VAT     |
| Aged Brass      | SESIFBOTMIN AB<br>310 Eur incl. VAT     |
| Burnished Brass | SESISESIFBOTMIN BB<br>310 Eur incl. VAT |
| Satin Nickel    | SESIFBOTMIN NS<br>360 Eur incl. VAT     |
| Black Nickel    | SESIFBOTMIN NNO<br>360 Eur incl. VAT    |
| Gold            | SESIFBOTMIN OR<br>430 Eur incl. VAT     |

#### Cleaning

Wipe the surface with a soft cloth and lukewarm water and possibly with soap solution. Avoid alkaline, acid-liming or abrasive cleaners. Brass is a material that over time gets a beautiful patina but can be polished with brass polish. Aged and Burnished Brass also gets patina but should not be polished. The galvanized surfaces retain their lustre.



## Installation Guide

### Preparation

- Ensure the area under the sink is clean and free of debris.
- Turn off the water supply to prevent leaks during installation.
- Verify that the sink's drain outlet and wall drainage outlet are properly aligned.

### Inspect the Components

- Unpack the bottle trap and inspect it for any visible damage.
- Identify all parts as per the installation drawing included with the product.

### Attach to the Sink Drain

- Connect the upper section of the bottle trap to the sink drain outlet.
- Tighten by hand, refrain from using any grappling tools as this can damage the surface finish.
- Avoid over-tightening to prevent damage.

### Adjust the Pipes

- Measure the required lengths for the vertical and horizontal pipes to fit your sink and drainage system.
- Cut the pipes to the appropriate lengths using a fine-tooth metal saw.
- Smooth the cut edges to avoid sharp ends or uneven surfaces.

### Connect to the Wall Drainage Outlet

- Align the horizontal pipe of the bottle trap with the wall drainage outlet.
- Insert the pipe into the outlet and secure it using the supplied mounting components.
- Check that the connection is firm and well aligned.

### Test for Leaks

- Turn on the water supply and run water through the sink.
- Inspect all connections for any leaks.
- Tighten further if leaks are found.

